


ENGINE DATASHEET



KOHLER®

Engine ref. : KD36V16-5BFP

General technical data

Cylinders configuration	V
Number of cylinders	16
Engine optimisation	Fuel optimisation
Dual Frequency	Yes
Speed (RPM)	1500
Speed (RPM)	1800
Displacement (L)	35,96
Bore (mm)	135
Stroke (mm)	157
Compression ratio	15 : 1
Engine Firing Order	1-15-6-13-8-4-16-7-11-5-9-2-14-10-3-12
Air inlet system	Turbo
Fuel	Diesel Fuel


Performance

	RPM	1500	1800
Maximum stand-by power at rated RPM (kW)		1238	1292
PRP Power (kW)		1125,50	1174,50
Pistons speed (m/s)		7,85	9,42
BMEP @ PRP 50 Hz (bar) / BMEP @ PRP 60 Hz (bar)		25	21,80
Friction Power Loss (kW)			
Max Combustion Pressure (Mpa)			

Electrical system

Governor type	Electronic
ECU type	KODEC
Frequency regulation, no-load to full-load	Isochrone
Frequency regulation, steady state (%)	+/- 0.25%
No. of teeth on ring gear	174
Idle speed (RPM)	1000
Battery voltages (V)	24
Charging alternator (V/A)	24 / 28 / 140
Starter characteristics (V/kW)	24 / 8.4

ENGINE DATASHEET



KOHLER®

Engine ref. : KD36V16-5BFP

Dimensions and weight

Length (mm)	2715
Width (mm)	1336
Height (mm)	1426
Dry weight (kg)	3200
Wet weight (kg)	3455
Center of Gravity from Rear Face of Block (mm)	760

Construction / Material

Main Bearing Type	Half shell bearing
Cylinder Head Material	Cast Iron
Crankshaft Material	Steel
Intake and Exhaust Valve Material	Steel
Piston type & material	Steel
Exhaust manifold type	Dry


Installation

Maximum Bending Moment at Rear Face of Block (RFOB) (Nm)	8000
Maximum Rear Bearing Load (N)	850
Maximal engine inclination, longitudinal front up/down (degree)	10
Maximal engine inclination, lateral (degree)	15
SAE Flywheel housing	0
SAE Flywheel	18
Inertia (kg.m ²)	8,26

Fuel system

	RPM	1500	1800
Maximum fuel pump flow (L/h)		267	278
Maximum fuel return flow (L/h)			
Maximum heat rejected to return fuel (kW)			
Max. restriction at fuel pump (m)		3,50	
Max head on fuel return line (m)		3,50	
Maximum allowed inlet fuel temperature (°C)		60	
Primary fuel filter rating (micron)		5	
Fuel Prefilter / Water Separator Micron Size		10	
Fuel Inlet Minimum recommended size (mm)			
Fuel Outlet Minimum recommended size (mm)			

ENGINE DATASHEET



KOHLER®

Engine ref. : KD36V16-5BFP

Fuel consumption (Specific fuel consumption +5% ; ISO3046-1 ; 42.7 MJ/kg)

	RPM	1500	1800
Specific consumption 25% PRP load (g/kW.h)		213	
Specific consumption 50% PRP load (g/kW.h)		197	
Specific consumption 75% PRP load (g/kW.h)		193	
Specific consumption 100% PRP load (g/kW.h)		196	197
Specific consumption 25% ESP load (g/kW.h)		210	
Specific consumption 50% ESP load (g/kW.h)		196	
Specific consumption 75% ESP load (g/kW.h)		192	
Specific consumption 100% ESP load (g/kW.h)		196	

Lubrication system

	RPM	1500	1800
Oil consumption 100% ESP (L/h)		0,15	0,15
Oil system capacity including filters (L)			152
Oil sump capacity (L)			135
Oil capacity between dipstick marks Max-Min (L)			20
Min. oil pressure (bar)			3,30
Oil Pressure at rated speed (bar)			
Max. oil pressure (bar)			
Oil temperature maximum (°C at 25°C ambient)			118
Oil filter micron size			14
Oil Filter Quantity and type			Spin On / 4
Oil cooler			Plate Exchanger


Air intake system

	RPM	1500	1800
Intake air flow (L/s)		1037	1317
Max. intake restriction (mm H2O)		500	500

Exhaust system

	RPM	1500	1800
Heat rejection to exhaust (kW)		797	797
Max. exhaust back pressure (mm H2O)		850	850
Exhaust gas temperature @ PRP 50Hz (°C)			544
Exhaust gas temperature @ PRP 60Hz (°C)			452
Exhaust gas flow @ PRP 50Hz (L/s)			3022
Exhaust gas flow @ PRP 60Hz (L/s)			3376

ENGINE DATASHEET



KOHLER®

Engine ref. : KD36V16-5BFP

Cooling system

	RPM	1500	1800
Radiated heat to ambient (kW)		79	
Heat rejection to coolant HT (kW)		446	440
Flow on the HT circuit at 0.7Bars pressure drop off engine (L/min)		1723	2232
Outlet coolant temperature (°C)		100	
Maximum Coolant temp without derating (°C)		105	
Max coolant temperature, Shutdown (°C)		105	
Coolant capacity HT, engine only (L)		124	
Restriction pressure drop off engine – HT circuit (mbar)		700	
Minimal pressure before HT pump (mbar)		600	
Max. pressure at inlet of HT water pump (mbar)		1000	
Thermostat begin of opening HT (°C)		82	
Thermostat end of opening HT (°C)		92	
HT Standard pressure cap setting (kPa)		100	
Water Pump Type		Vane Wheel pump	
Fan drive ratio		0.82	

Charge air cooling system

	RPM	1500	1800
CAC Heat Rejection (kW)		193	264
CAC Temperature into Engine at 25°C Limit, (°C min / max)		45	46
CAC Temperature into Engine Limit (max at any ambient temperature) (°C)		60	60
Compressor Discharge Temp at 25°C (°C)		193	205
Compressor Discharge Temp Max (°C)		225	
Maximum Pressure Drop through CAC (kPa)		10	15,10
Turbocharger Boost Pressure (kPa)		184	206