

DATASHEET ALTERNATOR

Alternator ref. KH00602T
 Alternator type KH00602TO4N



-GENERAL CHARACTERISTICS-

Voltage Type (V) 400/230 Altitude (m) 0-1000
 Number of Phase Three phase AVR Regulation Yes
 Number of pole 4 Indication of protection IP23

Capacity for maintaining short circuit at 3 In for 10 s Yes
 Winding type Standard

Efficiency & Power

Frequency (Hz) 50 Hz Nominal voltage (V) 400

	Class H				Class F	Class B
	125°C/ 40°C continuous	130°C/ 25°C standby	150°C/ 40°C standby	163°C/ 27°C standby	105°C/ 40°C continuous	80°C/ 40°C continuous
Nominal Rating(Kva)	40	40	42.5	45	36.5	32
Nominal Rating(KW)	32	32	34	36	29.2	25.6
Efficiency 100%	88.9	89	88.6	88.3	89.4	89.9

-ELECTRICAL CHARACTERISTICS-

Voltage regulation at established rating (+/- %) 0.5
 Insulation class H
 T° class (H/125°), continuous 40°C H / 125°K
 T° class (H/163°C), standby 27°C H / 163°K
 Wave form : NEMA=TIF <50
 Unbalanced load acceptance ratio (%) 100
 Number of wires 6
 Total Harmonic Distortion in no-load DHT (%) <3.5
 Wave form : CEI=FHT <2
 Total Harmonic Distortion, on linear load DHT (%) <5
 Technology Brushless
 L-L Harmonic Maximum - Single (%) 18
 Deviation Factor (%) 3
 Shaft Current
 Main Stator Capacitance to ground (mfd)

Reactances

Direct axis synchro reactance unsaturated (Xd) (%) 281
 Direct axis transient reactance saturated (X'd) (%) 14.8
 Direct axis subtransient reactance saturated (X''d) (%) 7.4
 Quadra axis synchro reactance unsaturated (Xq) (%) 143
 Quadra axis subtransient reactance saturated (X''q) (%) 10.6
 Zero sequence reactance unsaturated (Xo) (%) 0.6
 Negative sequence reactance saturated (X2) (%) 9.02

Short circuit ratio

Short circuit ratio (Kcc) 0.424
 Subtransient time constant (T''d) (ms) 5

3.351413E+10-E

The generator set manufacturer reserves the right to change the design or specifications without notice and without any obligation or liability whatsoever

DATASHEET ALTERNATOR

Alternator ref. KH00602T
Alternator type KH00602TO4N

KOHLER[®]

Short circuit transient time constant (T'd) (ms)	50
Open circuit time constant (T'do) (ms)	944
Subtransient time constant (T''q) (ms)	5
Leakage stator reactance (Xa)(%)	0.74
Stator Resistance (Ra)(%)	0.075
Armature time constant (Ta) (ms)	8
No load excitation current (io) (A)	0.56
Full load excitation current (ic) (A)	2.19
Full load excitation voltage (uc) (V)	32.1
Heat rejection (W)	3955.16
No load losses (W)	888.22
Stator resistance (for 20°C ambient) (Ω)	0.3023
Rotor resistance (for 20°C ambient) (Ω)	0.77813
Exciter resistance - stator/inductor (for 20° ambient) (Ω)	15.639
Exciter resistance - rotor/armature (for 20° ambient) (Ω)	0.225
Recovery time (Delta U = 20% transient) (ms)	500
Engine start (Delta U = 20% perm. or 30% trans.) (kVA)	98.53
Transient dip (4/4 load) - PF : 0,8 AR (%)	13

Additional electrical characteristics-

Winding X1, X2 auxiliary resistance (for 20° ambient) (Ω)	0
Auxiliary winding X1, X2 excitation voltage at no load (V)	0
Winding Z1, Z2 auxiliary resistance (for 20° ambient) (Ω)	0.61
Auxiliary winding Z1, Z2 excitation voltage at no load (V)	5.9

-MECHANICAL CHARACTERISTICS-

Number of bearing	1
Overspeed (rpm)	2250
Coupling	Direct

DATASHEET ALTERNATOR

Alternator ref. KH00602T
Alternator type KH00602TO4N

KOHLER[®]

-TECHNICAL CURVES-

Motor starting curve locked rotor (0,6PF)

Motor starting curve locked rotor (0,3PF)

DATASHEET ALTERNATOR

Alternator ref. KH00602T
Alternator type KH00602TO4N



Efficiencies curve (by excitation system)

Loading curve (by excitation system)

DATASHEET ALTERNATOR

Alternator ref. KH00602T
Alternator type KH00602TO4N

KOHLER[®]

Short circuit curve at no load and rated speed

Influence due to connection

Curves shown are for star (Y) connection

For other connections, use the following multiplication factors :

- Series delta : current value x 1.732
- Parallel star : current value x 2

Influence due to short-circuit

Curves are based on a three-phase short-circuit. For the other types of short-circuit, use the following multiplication factors :

(*) Capacity for maintaining short circuit at $3 I_n$ for 10 s = YES

DATASHEET ALTERNATOR

Alternator ref. KH00602T
Alternator type KH00602TO4N



Rejection curve (by excitation system)

Capability curve (PQ diagram)

DATASHEET ALTERNATOR

Alternator ref. KH00602T
Alternator type KH00602TO4N



DIMENSIONS-

Overall dimension drawing (Single bearing)

DATASHEET ALTERNATOR

Alternator ref. KH00602T
Alternator type KH00602TO4N



Overall dimension drawing (Two bearings)

DATASHEET ALTERNATOR

Alternator ref. KH00602T
Alternator type KH00602TO4N



-TORSIONAL ANALYSIS DATA-

Rotation part drawing for torsional vibration calculation (Single bearing)

DATASHEET ALTERNATOR

Alternator ref. KH00602T
Alternator type KH00602TO4N



Rotation part drawing for torsional vibration calculation (Two bearings)