

RATINGS 400 V - 50 Hz		
Standby	kVA	715
	kWe	572
Data Center / Mission Critical	kVA	715
	kWe	572
Prime	kVA	650
	kWe	520

### Benefits & features

#### KOHLER premium quality

- Design offices using the latest technical innovations
- Modern fully certified factories
- A cutting-edge laboratory
- The generating set, its components and a wide range of options have been fully developed, prototype tested, factory built, and production tested

#### KOHLER premium performances

- Optimized and certified sound levels
- Reliable power, even in extreme conditions
- Optimized fuel consumption
- Compact footprint
- Best quality of electricity, high starting and loading capacity, according to ISO8528-5
- Robust base frames and high-quality enclosures
- Protection of installations and people
- Approved in line with the most stringent standards

#### Engines

- Premium level engines, in-house or from strong partners
- High power density, small footprint
- Low temperature starting capability
- Long maintenance interval

#### Alternator

- Provide industry leading motor starting capability
- Made in Europe
- Excitation system to permit sustained overcurrent > 300% In, during 10 sec
- Built with a class H insulation and IP23

#### Cooling

- A flexible solution using an electrical driven radiator fan
- Designed or optimized by KOHLER
- High temperature and altitude product capacity available

#### Base frame and enclosure

- High quality steel with enhanced corrosion resistance
- Highly durable QUALICOAT-certified epoxy paint
- Minimum 1000 hours of resistance to salt spray in accordance with ISO12944
- Ergonomic access to allow easy maintenance and connection of the generator
- Robust design optimized for transportation

### GENERAL SPECIFICATIONS

Engine brand	VOLVO
Alternator commercial brand	KOHLER
Voltage (V)	400/230
Standard Control Panel	APM403
Consumption @ 100% load ESP (L/h)	143
Consumption @ 100% PRP load (L/h)	131.2
Type of Cooling	Mechanical driven fan
Performance class	G3

### GENERATOR SETS RATINGS

Voltage	Standby			Data Center / Mission Critical		Prime	
	kWe	kVA	Amps	kWe	kVA	kWe	kVA
415/240	572	715	995	572	715	520	650
400/230	572	715	1032	572	715	520	650
380/220	570	712	1082	570	712	518	647
240 TRI	572	715	1720	572	715	520	650
230 TRI	572	715	1795	572	715	520	650
220 TRI	570	712	1869	570	712	518	647

### DIMENSIONS COMPACT VERSION

Length (mm)	3470
Width (mm)	1630
Height (mm)	2048
Tank capacity (L)	610
Dry weight (kg)	4060

### DIMENSIONS SOUNDPROOFED VERSION

Type soundproofing	M230
Length (mm)	5023
Width (mm)	1630
Height (mm)	2672
Tank capacity (L)	610
Dry weight (kg)	5590

Distributed By:



HIRE - SALES - SERVICE

East Coast Generators Pty Ltd

83 - 89 Westgate Drive,  
Altona North, VIC 3025

Phone: 03 93698800

E-mail: sales@eastcoastgenerators.com.au

Web: www.eastcoastgenerators.com.au  
ABN 14 202 273 633, ACN 006 517 362

#### Engine

##### General

Engine brand	VOLVO
Engine ref.	TWD1644GE
Air inlet system	Turbo
Cylinders configuration	L
Number of cylinders	6
Displacement (L)	16.12
Bore (mm) * Stroke (mm)	144 * 165
Compression ratio	16.8 : 1
Speed (RPM)	1500
Maximum stand-by power at rated RPM (kW)	630
Charge Air coolant	Air/Water
Injection Type	Direct
Governor type	Electronic
Air cleaner type, models	Dry

##### Fuel system

Maximum fuel pump flow (L/h)	170
Max head on fuel return line (m)	2
Maximum allowed inlet fuel temperature (°C)	60

##### Consumption with cooling system

Consumption @ 100% load ESP (L/h)	143
Consumption @ 100% PRP load (L/h)	131.2
Consumption @ 75% PRP load (L/h)	98.4
Consumption @ 50% PRP load (L/h)	66.3

#### Emissions

##### Lubrication System

Oil system capacity including filters (L)	48
Min. oil pressure (bar)	
Max. oil pressure (bar)	5
Oil sump capacity (L)	42
Oil consumption 100% ESP 50Hz (L/h)	0.11

##### Air Intake system

Max. intake restriction (mm H2O)	500
Intake air flow (L/s)	702

##### Exhaust system

	PRP	ESP
Heat rejection to exhaust (kW)		432
Exhaust gas temperature (°C)	485	480
Exhaust gas flow (L/s)	1558	1667
Max. exhaust back pressure (mm H2O)	1000	

##### Cooling system

Radiator & Engine capacity (L)	151
Fan power 50Hz (kW)	21
Fan air flow w/o restriction (m3/s)	11.4
Available restriction on air flow (mm H2O)	20
Type of coolant	Glycol-Ethylene
Radiated heat to ambient (kW)	24
Heat rejection to coolant HT (kW)	228
Max coolant temperature, Shutdown (°C)	107
Thermostat begin of opening HT (°C)	82
Thermostat end of opening HT (°C)	92

Distributed By:



HIRE - SALES - SERVICE

East Coast Generators Pty Ltd

83 - 89 Westgate Drive,  
Altona North, VIC 3025

Phone: 03 9369 8800

E-mail: sales@eastcoastgenerators.com.au  
Web: www.eastcoastgenerators.com.au  
ABN 14 202 273 633, ACN 006 517 362

#### Alternator Specifications

Alternator commercial brand	KOHLER
Alternator ref.	KH02401T
Number of pole	4
Number of bearing	Single Bearing
Technology	Brushless
Indication of protection	IP23
Insulation class	H
Number of wires	6
Capacity for maintaining short circuit at 3 In for 10 s	Yes
AVR Regulation	Yes
Coupling	Direct


#### Application data

Overspeed (rpm)	2250
Power factor (Cos Phi)	0.8
Voltage regulation at established rating (+/- %)	0.50
Wave form : NEMA=TIF	<50
Wave form : CEI=FHT	<2
Total Harmonic Distortion in no-load DHT (%)	<4
Total Harmonic Distortion, on linear load DHT (%)	<4
Recovery time (Delta U = 20% transient) (ms)	500

#### Performance datas

Continuous Nominal Rating 40°C (kVA)	660
Unbalanced load acceptance ratio (%)	60

Peak motor starting (kVA) based on x% voltage dip power factor at 0.3



#### Alternator Standard Features

- All models are brushless, rotating-field alternators
- NEMA MG1, IEEE, and ANSI standards compliance for temperature rise and motor starting
- The AVR voltage regulator provides superior short circuit capability
- Self-ventilated and dip proof construction
- Sustained short-circuit current of up to 300% of the rated current for up to 10 seconds
- Superior voltage waveform

*Note: See Alternator Data Sheets for alternator application data and ratings, efficiency curves, voltage dip with motor starting curves, and short circuit decrement curves.*

Distributed By:



**East Coast Generators Pty Ltd**

83 - 89 Westgate Drive,  
Altona North, VIC 3025

Phone: 03 93698800

E-mail: sales@eastcoastgenerators.com.au  
Web: www.eastcoastgenerators.com.au  
ABN 14 202 273 633, ACN 006 517 362

**Dimensions compact version**

---

Length (mm) * Width (mm) * Height (mm)	3470 * 1630 * 2048
Dry weight (kg)	4060
Tank capacity (L)	610

**Dimensions soundproofed version**

---

**M230**

Length (mm) * Width (mm) * Height (mm)	5023 * 1630 * 2672
Dry weight (kg)	5590
Tank capacity (L)	610
Acoustic pressure level @1m in dB(A) 50Hz (75% PRP)	85
Measured acoustic power level (Lwa) 50Hz (75% PRP)	105
Acoustic pressure level @7m in dB(A) 50Hz (75% PRP)	75

**Dimensions DW compact version**

---

Length (mm) * Width (mm) * Height (mm)	5083 * 1680 * 2308
Dry weight (kg)	4690
Tank capacity (L)	1950

**Dimensions DW soundproofed version**

---

**M230 DW**

Length (mm) * Width (mm) * Height (mm)	5083 * 1690 * 2932
Dry weight (kg)	6180
Tank capacity (L)	1950
Acoustic pressure level @1m in dB(A) 50Hz (75% PRP)	85
Measured acoustic power level (Lwa) 50Hz (75% PRP)	105
Acoustic pressure level @7m in dB(A) 50Hz (75% PRP)	75

Distributed By:

**HIRE - SALES - SERVICE****East Coast Generators Pty Ltd**83 - 89 Westgate Drive,  
Altona North, VIC 3025

Phone: 03 93698800

E-mail: sales@eastcoastgenerators.com.au

Web: www.eastcoastgenerators.com.au  
ABN 14 202 273 633, ACN 006 517 362

#### Basic terminal block



It is used as a basic terminal block for connecting a control unit. Offers the following functions:

- emergency stop button
- customer connection terminal block
- CE certified


#### M80



The M80 is a dual-function control panel. It can be used as a basic terminal block for connecting a control unit and as an instrument panel with a direct read facility, with displays giving a global view of your generating set's basic parameters. Offers the following functions:

- Engine parameters: tachometer, working hours counter, coolant temperature indicator, oil pressure indicator
- emergency stop button
- customer connection terminal block
- CE certified

#### APM403



#### BASIC GENERATING SET AND POWER PLANT CONTROL

The APM403 is a versatile control unit which allows operation in manual or automatic mode

- Measurements : voltage and current
- kW/kWh/kVA power meters
- Standard specifications: Voltmeter, Frequency meter.
- Optional : Battery ammeter.
- J1939 CAN ECU engine control
- Alarms and faults: Oil pressure, Coolant temperature, Overspeed, Start-up failure, alternator min/max, Emergency stop button.
- Engine parameters: Fuel level, hour counter, battery voltage.
- Optional (standard at 24V): Oil pressure, water temperature.
- Event log/ Management of the last 300 genset events.
- Mains and genset protection
- Clock management
- USB connections, USB Host and PC,
- Communications : RS485 INTERFACE
- ModBUS protocol /SNMP
- Optional : Ethernet, GPRS, remote control, 3G, 4G,
- Websupervisor, SMS, E-mails

#### APM802



#### ADVANCED POWER PLANT MANAGEMENT CONTROL

Dedicated to power plant management APM802 provides advanced control, system monitoring, and system diagnostics for optimum performance and compatibility

- Graphic display with touchscreen
- User language selectable
- Specially researched ergonomics
- High level of equipment availability
- USB and Ethernet ports
- Modbus protocol
- Making it easy to extend the installation
- Complies with the international standard IEC 61131-3

Distributed By:



HIRE - SALES - SERVICE

East Coast Generators Pty Ltd

83 - 89 Westgate Drive,  
Altona North, VIC 3025

Phone: 03 93698800

E-mail: sales@eastcoastgenerators.com.au

Web: www.eastcoastgenerators.com.au  
ABN 14 202 273 633, ACN 006 517 362

**STANDARD SCOPE OF SUPPLY**

All our gensets are fitted with:

- Industrial water cooled DIESEL engine
- Electric starter & charge alternator
- Standard air filter
- Schneider or ABB electric circuit breaker, adapted to the short-circuit current of the generating set
- Single bearing alternator IP 23 T° rise/ insulation to class H/H
- Welded steel base frame with 85% vibration attenuation mounts
- 4 lifting points on the chassis, lifting bar on the top included from 165 kVA ESP or optional
- highly durable QUALICOAT certified epoxy paint
- frame height optimized to allow it to be moved safely by forklift
- enclosure made of new high-quality European steel with enhanced corrosion resistance
- IP 64 locks, made from stainless materials
- enclosures and base frames tested and analyzed by the French Corrosion Institut
- 100% of tanks tested for permeability
- Personal protection ensured by protective grilles on hot and rotating parts
- Separate 9 dB(A) silencer
- Fuel tank welded inside the genset frame
- Retention bund included for gensets up to 110 kVA ESP
- Charged DC starting battery with electrolyte
- Emergency stop button on the outside
- Flexible fuel lines & lub oil drain cock
- Exhaust outlet with flexible and flanges
- User's manual (1 copy)
- Packing under plastic film
- Delivered with oil and antifreeze liquid

**CODES AND STANDARDS**

Engine-generators set is designed and manufactured in facilities certified to standards ISO9001:2015 & ISO14001:2015. The generator sets and its components are prototype-tested, factory built and production tested and are in compliance with the relevant standards:

- Machinery Directive 2006/42/EC of May 17th 2006
- EMC Directive 2014/30/UE
- Safety objectives set out in the Low Voltage Directive 2014/35/UE
- EN ISO 8528-13, EN 60034-1, EN 61000-6-1, EN 61000-6-2, EN 61000-6-3, EN 55011, EN 1679-1 et EN 60204-1

**POWER RATINGS DEFINITION according to ISO8528-1 (2018-02 edition) and ISO-3046-1**

**Emergency Standby Power (ESP):** The standby rating is applicable to varying loads for the duration of a power outage. There is no overload capability for this rating. Average load factor per 24 hours of operation is <85%.

**Prime Power (PRP):** At varying load, the number of generator set operating hours is unlimited. A 10% overload capacity is available for one hour within 12 hour of operation. Average load factor per 24 hours of operation is <75%.

**Data Center Power (DCP):** Data center power is defined as being the maximum power which a generating set is capable of delivering while supplying a variable or continuous electrical load and during unlimited run hours. Depending on the sites to supply and the availability of reliable utility, the generating set manufacturer is responsible to define what power level is able to supply to fulfil that requirement including hardware or software or maintenance plan adaptation.

Distributed By:



**HIRE - SALES - SERVICE**

**East Coast Generators Pty Ltd**

83 - 89 Westgate Drive,  
Altona North, VIC 3025

Phone: 03 93698800

E-mail: sales@eastcoastgenerators.com.au  
Web: www.eastcoastgenerators.com.au  
ABN 14 202 273 633, ACN 006 517 362

**TERMS OF USE**

According to the standard, the nominal power assigned by the genset is given for 25°C Air Inlet Temperature, of a barometric pressure of 100 kPA (100 m A.S.L), and 30% relative humidity. For particular conditions in your installation, refer to the derating table.

**WARRANTY INFORMATIONS**

Standard Warranty Period:

- for Products in "back-up" service
  - o 30 months from the date the Product leaves the plant
  - o 24 months from the Product's commissioning date
  - o 1,000 running hours

The warranty expires when one of the above conditions is met.

- for Products in "prime" or "continuous" service (continuous supply of electricity, either in the absence of any normal electricity grid or to complement the grid),
  - o 18 months from the date the Product leaves the plant
  - o 12 months from the Product's commissioning date
  - o 2,500 running hours

The warranty expires when one of the above conditions is met.

For more details regarding conditions of application and scope of the warranty please refer to our General "terms & conditions of sales".

**Reference Conditions: 25°C Air Inlet Temperature, 40°C Fuel Inlet Temperature, 100 kPa Barometric Pressure; 10.7 g/kg of dry air Humidity. Intake Restriction set to maximum allowable limit for clean filter; Exhaust Back pressure set to maximum allowable limit.**

**Data was taken from a single engine test according to the test methods, fuel specification and reference conditions stated above and is subjected to instrumentation and engine-to-engine variability. Test conducted with alternate test methods, instrumentation, fuel or reference conditions can yield different results. Data and specifications subject to change without notice.**

Distributed By:



**HIRE - SALES - SERVICE**

**East Coast Generators Pty Ltd**

83 - 89 Westgate Drive,  
Altona North, VIC 3025

Phone: 03 93698800

E-mail: [sales@eastcoastgenerators.com.au](mailto:sales@eastcoastgenerators.com.au)

Web: [www.eastcoastgenerators.com.au](http://www.eastcoastgenerators.com.au)  
ABN 14 202 273 633, ACN 006 517 362