



Generator Specification Sheet - 100KVA Super Silenced Generator

Ultra-quiet generator with full paralleling capability ideal for Events, Film and TV Production power, Supply Authorities and any application where noise is a concern



100KVA Super Silent

Electrical Data

Rated Output	KVA	100
Rated Voltage	V	240/415
Rated Frequency	Hz	50
Rated Current	A	139
Outlets a (1 phase)		3 x 15 amp
(3 Phase)		2 x 32 amp 1 x 50 amp 1 x 63 amp 1 x 125 amp

Engine

		Perkins
Model		1104C-44TAG2
No of cylinders		4
Displacement	L	4.41
Rated output @ 1500RPM	KW	92.4
Fuel Type		Diesel
Fuel Capacity	L	300
Fuel Consumption b	L/Hour	17.3

Sound Level

Sound Level @ 7 Mtrs	dB(A)	54
----------------------	-------	----

Dimensions & Weight

Dimensions (LxWxH)	mm	2680 x 1130 x 1805
Approx Wet Weight	Kg	2120

General Characteristics

Shutdowns		Full Comap COMBI Spec paralleling control system.
Bundling		YES
Protection		Lockable Battery Isolator and Emergency Stop

- a. Outlet combination shown here is typical. Outlet requirements may differ from machine to machine
b. Fuel consumption figures are based on 75% load as per industry specifications

