



Generator Specification Sheet - 15 to 20KVA

Small, quiet, fuel-efficient diesel generators provide reliable power for multiple applications, from work sites and backup supplies to remote location film production, festivals and concerts.



15 to 20KVA

15KVA (Single Phase)

17KVA

20KVA

| Electrical Data | | SQ1150 | QAS16 | DGA20E |
|--------------------------------|-----|------------|------------|------------|
| Rated Output | KVA | 15 | | 20 |
| Rated Voltage | V | 240 | 240/415 | 240/415 |
| Rated Frequency | Hz | | 50 | |
| Rated Current | A | 63 | | |
| Outlets ^a (1 phase) | | 3 x 15 amp | 3 x 15 amp | 3 x 15 amp |
| (3 Phase) | | N/A | 1 x 32 amp | 1 x 32 amp |

| Engine | | V2203-EBG | Isuzu 4LE1 |
|------------------------|--------|-----------|------------|
| Model | | V2203-EBG | Isuzu 4LE1 |
| No of cylinders | | 4 | 4 |
| Displacement | L | 2.197 | 2.179 |
| Rated output @ 1500RPM | KW | 18.4 | 19.1 |
| Fuel Type | | Diesel | |
| Fuel Capacity | L | 100 | 140 |
| Fuel Consumption | L/Hour | 4.1 | 3.9 |

| Sound Level | | 63 | 51 |
|----------------------|-------|----|----|
| Sound Level @ 7 Mtrs | dB(A) | 63 | 51 |

| Dimensions & Weight | | 1725x795x118 | 1430x785x1440 |
|---------------------|----|--------------|---------------|
| Dimensions (LxWxH) | mm | 1725x795x118 | 1430x785x1440 |
| Approx Wet Weight | Kg | 915 | 980 |

- a. Outlet combination shown here is typical. Outlet requirements may differ from machine to machine
- b. Fuel consumption figures are based on 75% load as per industry specifications